



## S6500 (24L) 230V 50HZ



Showing the excellence of Pramac's professional equipment, this generator offers a robust package with a modern and economical Diesel engine. Perfect for intensive use, it's equipped with a control panel which allows to integrate many accessories and options for better confort and for optimal command.

### Main Features

Frequency	Hz	50
Voltage	V	230
Power factor	cos $\phi$	0.9
Phase and connection		1

### Power Rating

Standby power LTP	kVA	5.9
Standby power LTP	kW	5.3
Continuous power COP	kVA	4.8
Continuous power COP	kW	4.4

#### Ratings definition (According to standard ISO8528 1:2005)

**COP** - Continuous Power: It is defined as being the maximum power which a generating set is capable of delivering continuously for an unlimited number of hours, with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.

**LTP** - Limited-Time running Power: It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 h of operation per year (whose no more than 300 for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

### Engine specifications

Engine manufacturer		Yanmar
Model		L100N Electric
Engine cooling system		Air
Displacement	cm <sup>3</sup>	435
Aspiration		Natural
Operating Speed-Nominal	rpm	3000
Speed governor		Mechanical
Fuel		Diesel
Oil capacity	l	1.6
Starting system		Electric



### Alternator Specifications

Class		H
Voltage regulation system		Capacitor
IP protection		23
Poles		2
Frequency	Hz	50
Voltage tolerance	%	+5; -10 (cosφ1)

### Dimensional data

Length	(L) mm	840
Width	(W) mm	641
Height	(H) mm	696
Dry weight	Kg	114
Fuel tank capacity	l	24

### Autonomy

Fuel consumption @ 75% PRP	l/h	1.46
Fuel consumption @ 100% PRP	l/h	1.94
Running time @ 75% PRP	h	16.44
Running time @ 100% PRP	h	12.37