


PROUDLY 100% AUSTRALIAN OWNED

**MACFARLANE
GENERATORS**



VIC 136 Fairbank Road NSW: 1 St James Place QLD: 31 South Pine Road
Clayton South, Vic 3169 Seven Hills, Nsw 2147 Brendale, Qld 4500

Tel: 1300 MAC GEN (622 436) Email info@macgen.com

ESTABLISHED 1949

www.macfarlanegenerators.com.au

P11000 400V 50HZ



Low noise level, it is the ideal generator for use in residential areas or outside normal working hours. It's equipped with a reliable Diesel engine, first class components and complete instrumentation.

Main Features

Frequency	Hz	50
Voltage	V	400
Power factor	$\cos \phi$	0.8
Phase and connection		3

Power Rating

Standby power LTP	kVA	10.8
Standby power LTP	kW	8.6
Continuous power COP	kVA	10.0
Continuous power COP	kW	8.0

Single Phase Power Rating

Single phase standby power LTP	kVA	6.6
Single phase continuous power COP	kVA	6.0

Ratings definition (According to standard ISO8528 1:2005)

Engine specifications

Engine manufacturer	Yanmar	
Model	3TNV70-HGE	
Engine cooling system	Water	
Displacement	cm ³	854
Aspiration	Natural	
Operating Speed-Nominal	rpm	3000
Speed governor	Mechanical	
Fuel	Diesel	
Oil capacity	l	3.8
Coolant capacity	l	0.9
Starting system	Electric	
Electric circuit	V	12



Alternator Specifications

Class	H	
Voltage regulation system	Compound	
IP protection	23	
Poles	2	
Frequency	Hz	50

Dimensional data

Length	(L) mm	1400
Width	(W) mm	650
Height	(H) mm	975
Dry weight	Kg	325
Fuel tank capacity	l	24

Autonomy

Fuel consumption @ 75% PRP	l/h	2.65
Fuel consumption @ 100% PRP	l/h	3.45
Running time @ 75% PRP	h	9.06
Running time @ 100% PRP	h	6.96

Noise level

Guaranteed noise level (LWA)	dB(A)	96
Noise pressure level @ 7 mt	dB(A)	68