POWERLINK EP Perkins Series Diesel Generator with Leroy Somer Alternator



Model: WPS135S-AU

Frequency: **50Hz**Fuel type: **Diesel**

Powered by: **PERKINS SERIES**

415/240V-50Hz-3Phase

- Powerful heavy-duty Perkins industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service

TECHNICAL SPECIFICATIONS

Model	WPS135S-AU			
Power(ESP)	kVA/kw	150/120		
Power(PRP)	kVA/kw	135/108		
Voltage	V	415/240		
Fuel Consumption	Litre/hour	Fuel consumption	100% (of the Prime Power)	30.28 L/h
		Fuel consumption	75% (of the Prime Power)	22.7 L/h
		Fuel consumption	50% (of the Prime Power)	15.9 L/h
		Fuel consumption	25% (of the Prime Power)	9L/h
Fuel Tank Capacity	Litre	1087		<u> </u>
Noise Level	dB(A)@7m	-		
Dimensions and Weight	Length	Width	Height	Weight
	3338 mm	1262 mm	2153 mm	2659 kg

ENGINE SPECIFICATIONS

Manufacturer	Perkins
Model	1106A-70TG1
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	6
Displacement	7.01L
Bore and Stroke	105 mm × 135 mm
Compression Ratio	18.2
Frequency Regulation, steady state	±0.5%
Governor Type	Mechanical
Total Oil Capacity w/Filters	16.5 L
Coolant Capacity - Engine	9.5 L



ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer LSA44.3L10
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless, SHUNT
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	R250
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow	0.25m³/s(50Hz)
-----------------	----------------

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

Powerlink PLC7420

KEY FEATURES

- Microprocessor control, with high stability and credibility
- Monitoring and measuring operational parameters of the mains supply and genset
- Indicating operation status, fault conditions, all parameters and alarms
- Multiple protections; multiple parameters display, like
- pressure, temp. etc.
- Manual, automatic and remote work mode selectable
- Real time clock for time and date display, overall runtime display, 250 log entries
- Overall power output display
- · Integral speed/frequency detecting, telling status of
- start, rated operation, overspeed etc.
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol





MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED