# POWERLINK EP Perkins Series Diesel Generator with Leroy Somer Alternator



Model: WPS150BS-AU

Frequency: **50Hz**Fuel type: **Diesel** 

Powered by: **PERKINS SERIES** 

 Powerful heavy-duty Perkins industrial diesel and low emissions engine

- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service

# 415/240V-50Hz-3Phase

### **TECHNICAL SPECIFICATIONS**

WPS150BS-AU			
kVA/kw	165/132		
kVA/kw	150/120		
V	415/240		
Litre/hour	Fuel consumption1	00% (of the Prime Power)	33.4 L/h
	Fuel consumption 7	'5% (of the Prime Power)	24.7 L/h
	Fuel consumption 5	50% (of the Prime Power)	16.4 L/h
	Fuel consumption2	25% (of the Prime Power)	9.1 L/h
Litre	950L		
dB(A)@7m	73.7dBA		
Length	Width	Height	Weight
3518 mm	1142 mm	2088 mm	2666 kg
	kVA/kw kVA/kw V Litre/hour  Litre dB(A)@7m Length	kVA/kw         165/132           kVA/kw         150/120           V         415/240           Litre/hour         Fuel consumption1           Fuel consumption5         Fuel consumption5           Litre         950L           dB(A)@7m         73.7dBA           Length         Width	kVA/kw 165/132 kVA/kw 150/120 V 415/240 Litre/hour Fuel consumption100% (of the Prime Power) Fuel consumption5% (of the Prime Power) Fuel consumption50% (of the Prime Power) Fuel consumption25% (of the Prime Power) Litre 950L dB(A)@7m 73.7dBA Length Width Height

## **ENGINE SPECIFICATIONS**

Manufacturer	Perkins
Model	1106A-70TAG2
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	6
Displacement	7.01 L
Bore and Stroke	105 mm × 135 mm
Compression Ratio	18.2
Intake Resistance	≦8kPa
Governor Type	Mechanical
Total Oil Capacity w/Filters	18.0 L
Coolant Capacity	20.5L



### **ALTERNATOR SPECIFICATIONS**

Manufacturer	Leroy Somer LSA44.2M95
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	R250
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



### **AIR SYSTEM**

Engine Air Flow	0.37m <sup>3</sup> /s(50Hz)

Note: All data sheets are for reference only and subject to change without prior notice.

### **CONTROL PANEL**

Powerlink PLC7420
-------------------

### **KEY FEATURES**

- · Microprocessor control, with high stability and credibility
- Monitoring and measuring operational parameters of the mains supply and genset
- Indicating operation status, fault conditions, all parameters and alarms
- Multiple protections; multiple parameters display, like
- pressure, temp. etc.
- Manual, automatic and remote work mode selectable
- Real time clock for time and date display, overall runtime display, 250 log entries
- Overall power output display
- · Integral speed/frequency detecting, telling status of
- start, rated operation, overspeed etc.
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol





# MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED