POWERLINK EP Perkins Series Diesel Generator with Leroy Somer Alternator



Model: WPS180BS-AU

Frequency: **50Hz**Fuel type: **Diesel**

Powered by: **PERKINS SERIES**

- Powerful heavy-duty Perkins industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service

415/240V-50Hz-3Phase

TECHNICAL SPECIFICATIONS

WPS180BS-AU			
kVA/kw	198/158		
kVA/kw	180/144		
V	415/240		
Litre/hour	Fuel consumption 100% (of the P		39.6 L/h
	Fuel consumption	Fuel consumption 75% (of the Prime Power)	
	Fuel consumption	Fuel consumption 50% (of the Prime Power)	
	Fuel consumption	Fuel consumption 25% (of the Prime Power)	
Litre	950		
dB(A)@7m	72.1		
Length	Width	Height	Weight
3468 mm	1142 mm	2093 mm	2820.06 kg
	kVA/kw kVA/kw V Litre/hour Litre dB(A)@7m Length	kVA/kw 198/158 kVA/kw 180/144 V 415/240 Litre/hour Fuel consumption Fuel consumption Fuel consumption Fuel consumption Litre 950 dB(A)@7m 72.1 Length Width	kVA/kw 198/158 kVA/kw 180/144 V 415/240 Litre/hour Fuel consumption100% (of the Prime Power) Fuel consumption5% (of the Prime Power) Fuel consumption50% (of the Prime Power) Fuel consumption25% (of the Prime Power) Litre 950 dB(A)@7m 72.1 Length Width Height

ENGINE SPECIFICATIONS

Manufacturer	Perkins
Model	1106A-70TAG3
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	6
Displacement	7.01L
Bore and Stroke	105 mm × 135 mm
Compression Ratio	16.5
Frequency Regulation, steady state	±0.5%
Governor Type	Direct
Total Oil Capacity w/Filters	16.5 L
Coolant Capacity	20.5 L



ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer LAS44.3VL13
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless, SHUNT
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	R250
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow	0.37m ³ /s(50Hz)

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

ComAp	InteliLite 4 AMF9
Comp	III TO THE TO THE TOTAL TOTAL TO THE TOTAL TOTAL TO THE T

KEY FEATURES

- Easy configuration with InteliConfig
- Remote monitoring
- Cyber security by design
- Easy troubleshooting
- Built-in PLC logic
- Flexible platform
- Stand-by and prime power application control
- Zero power mode
- Secure user management





MELBOURNE | SYDNEY | BRISBANE | PERTH

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED