POWERLINK EP Perkins Series Diesel Generator with Leroy Somer Alternator



Model: WPS300S-AU

Frequency: **50Hz**Fuel type: **Diesel**

Powered by: **PERKINS SERIES**

 Powerful heavy-duty Perkins industrial diesel and low emissions engine

- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service

415/240V-50Hz-3Phase

TECHNICAL SPECIFICATIONS

Model	WPS300S-AU			
Power(ESP)	kVA/kw	330/264		
Power(PRP)	kVA/kw	300/240		
Voltage	V	415/240		
Fuel Consumption	Litre/hour	Fuel consumption	100% (of the Prime Power)	65 L/h
		Fuel consumption	n75% (of the Prime Power)	48 L/h
		Fuel consumption	n50% (of the Prime Power)	33 L/h
		Fuel consumption	n25% (of the Prime Power)	N/A
Fuel Tank Capacity	Litre	1650		
Noise Level	dB(A)@7m	-		
Dimensions and Weight	Length	Width	Height	Weight
	3970 mm	1362 mm	2334 mm	3738 kg

ENGINE SPECIFICATIONS

Manufacturer	Perkins
Model	1506A-E88TAG5
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	6
Displacement	8.8 L
Bore and Stroke	112 mm × 149 mm
Compression Ratio	16.1
Frequency Regulation, steady state	±0.5%
Governor Type	Electronic Fuel Injection
Total Oil Capacity w/Filters	41L
Coolant Capacity	40 L



ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer LSA46.3L10
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless, SHUNT
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	R250
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow	0.48m³/s(50Hz)
-----------------	----------------

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

Powerlink PLC7420

KEY FEATURES

- · Microprocessor control, with high stability and credibility
- Monitoring and measuring operational parameters of the mains supply and genset
- Indicating operation status, fault conditions, all parameters and alarms
- Multiple protections; multiple parameters display, like
- pressure, temp. etc.
- Manual, automatic and remote work mode selectable
- Real time clock for time and date display, overall runtime display, 250 log entries
- · Overall power output display
- · Integral speed/frequency detecting, telling status of
- start, rated operation, overspeed etc.
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol





www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED