# **POWERLINK EP Perkins Series Diesel Generator with Leroy Somer Alternator**



WPS350S-AU Model:

Frequency: **Diesel** Fuel type:

Powered by: **PERKINS SERIES** 

50Hz

• Intelligent control - Manual & Remote start

Powerful heavy-duty Perkins industrial diesel

- Weather protective and sound attenuated enclosure
- Comprehensive warranty and service

and low emissions engine

## 415/240V-50Hz-3Phase

#### **TECHNICAL SPECIFICATIONS**

Model	WPS350S-AU			
Power(ESP)	kVA/kw	385/308		
Power(PRP)	kVA/kw	350/280		
Voltage	V	415/240		
Fuel Consumption	Litre/hour	Fuel consumption 100% (of the Prime Power)		76 L/h
		Fuel consumption	75% (of the Prime Power)	59 L/h
		Fuel consumption 50% (of the Prime Power)		41L/h
		Fuel consumption25% (of the Prime Power)		N/A
Fuel Tank Capacity	Litre	1650		
Noise Level	dB(A)@7m	80.1		
Dimensions and Weight	Length	Width	Height	Weight
	4242 mm	1573 mm	2476 mm	4659 kg

#### **ENGINE SPECIFICATIONS**

Manufacturer	Perkins	
Model	2206C-E13TAG2	
Engine Speed Rated	1500 RPM	
Cylinder /Arrangement	6	
Displacement	12.5 L	
Bore and Stroke	130 mm × 157 mm	
Compression Ratio	16.3	
Frequency Regulation, steady state	±0.5%	
Governor Type	Electronic Fuel Injection	
Total Oil Capacity w/Filters	40 L	
Coolant Capacity	51.4 L	



#### **ALTERNATOR SPECIFICATIONS**

Manufacturer	Leroy Somer LSA46.3L11
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless, SHUNT
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	R250
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



#### **AIR SYSTEM**

Engine Air Flow 0.9m³/s(50Hz)
-------------------------------

Note: All data sheets are for reference only and subject to change without prior notice.

#### **CONTROL PANEL**

Powerlink	PLC7420
Powerlink	PLC/420

#### **KEY FEATURES**

- · Microprocessor control, with high stability and credibility
- Monitoring and measuring operational parameters of the mains supply and genset
- Indicating operation status, fault conditions, all parameters and alarms
- · Multiple protections; multiple parameters display, like
- pressure, temp. etc.
- Manual, automatic and remote work mode selectable
- Real time clock for time and date display, overall runtime display, 250 log entries
- Overall power output display
- · Integral speed/frequency detecting, telling status of
- start, rated operation, overspeed etc.
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol





### MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED