

DG13KSEm

Diesel Generator

Single Phase



Model: **DG13KSEm**
 Frequency: **50Hz**
 Fuel type: **Diesel**
 Phase: **Single**
 Standby: **13kVA**

- Reliable heavy-duty industrial diesel and low emissions engine
- Standard ComAp electronic control system with remote start/stop function
- Sound reduced and weather protected enclosure
- Comprehensive warranty and service

TECHNICAL SPECIFICATIONS

Model	DG13KSEm			
Prime Power	kVA/kW	12/12		
Standby Power	kVA/kw	13/13		
Power Factor		1		
Rate Voltage	V	230		
Fuel Consumption	Kg/hour	Fuel consumption100% (of the Prime Power)	4.2	
		Fuel consumption75% (of the Prime Power)	3.2	
		Fuel consumption50% (of the Prime Power)	2.3	
		Fuel consumption25% (of the Prime Power)	1.4	
Fuel Tank Capacity (Base Frame)	Litre	77.5		
Running Time	Hour	14		
Noise Level	dB(A)@7m	69		
Dimensions and Weight	Length	Width	Height	Weight
	1900 mm	900 mm	1120 mm	785 kg

ENGINE SPECIFICATIONS

Model	D485
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	4 / Inline
Displacement	2.2 mm
Bore and Stroke	85 mm × 95 mm
Compression Ratio	18
Aspiration	Natural
SAE	4/7.5
Lubricant Capacity	6 L
Cooling	Water

PROUDLY 100% AUSTRALIAN OWNED

MACFARLANE
GENERATORS
ESTABLISHED 1949

Power Anywhere Anytime | DG13KSEm | 12.2020

MACFARLANEGENERATORS.COM.AU

ALTERNATOR SPECIFICATIONS

Model	164D
Structure	Single Bearing, Brushless
Excitation Mode	Self Excitation
Protection Class	IP23
Insulation Class	H
TIF	>50
THF	<2%
Air Flow	0.071 m ³ /s
AVR model	SX460

EXHAUST SYSTEM

Exhaust Gas Flow	6 m ³ /min
Exhaust Gas Temperature	400°C
Max Back Pressure	5 kPa

AIR SYSTEM

Engine Air Flow	2 m ³ /min
-----------------	-----------------------

COOLANT SYSTEM

Coolant Capacity	6L
------------------	----

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

InteliLite	MRS10
------------	-------

KEY FEATURES

- Compact gen-set controller for single operating genset
- Manual and remote start capability
- Full gen-set monitoring and protection
- Multiple languages (user changeable) in controller
- Plug-in module concept for more capabilities (RS232, RS485, USB and Internet)
- True RMS measurement
- 6 binary outputs, 6 binary inputs, 3 configurable analog inputs
- Fault history



PROUDLY 100% AUSTRALIAN OWNED

MACFARLANE GENERATORS

ESTABLISHED 1949

POWER ANYWHERE ANYTIME

MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com
SALES | SERVICE | SPARES | HIRE | NEW | USED

DG13KSEm | 12.2020