PowerLink RK Kubota Series Diesel Generator with Leroy Somer Alternator



Model:**PK10S-AU**Frequency:**50Hz**Fuel type:**Diesel**Powered by:**KUBOTA Engine**

TECHNICAL SPECIFICATIONS

- Powerful heavy-duty Kubota industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service
- Outlet 4 x 15A

Model	PK10S-AU	PK10S-AU			
Power(ESP)	kVA/kW	11/8.8			
Power(PRP)	kVA/kW	10/8	10/8		
Structure Type		RS			
Fuel Consumption	Litre/hour	Fuel consumption 100% (of the Prime Power) 3.5 L/h			
		Fuel consumption 75% (of the Prime Power) 2.9 L/h			
		Fuel consumption 50% (of the Prime Power) 1.8 L/h			
		Fuel consumption25% (of the Prime Power) N/A			
Fuel Tank Capacity	Litre	100	100		
Noise Level	dB(A)@7m	64.7	64.7		
Dimensions and Weight	Length	Width Height Weight			
	1932 mm	927 mm 1308 mm 700 kg			

ENGINE SPECIFICATIONS

Manufacturer	Kubota
Model	D1105-BG
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	3
Displacement	1.123 L
Bore and Stroke	78 mm × 78.4 mm
Compression Ratio	22
Intake Resistance	1.96kPa
Type of Injection	Direct
Total Oil Capacity	5.1L
Coolant Capacity	6.4 L



ALTERNATOR SPECIFICATIONS

Manufacturer	Stamford PI044H
Phase	1
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation : Class, temperature rise	Н
Degree of protection	IP23
AVR	Yes
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow

0.11 m³/s(50Hz)

PLC-920

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

PowerLink

KEY FEATURES

- Standard Control Function
- Manual Engine Control Module
- Low Oil Pressure
- High Engine Temperature
- Auxiliary Shutdown
- Over Speed Protection
- Protection Hold-off Timer
- Charge Failure Warning





MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED

POWER ANYWHERE ANYTIME