

PowerLink RK Kubota Series Diesel Generator with Stamford Alternator



Model: **PK10S-AU**
 Frequency: **50Hz**
 Fuel type: **Diesel**
 Powered by: **KUBOTA Engine**

- Powerful heavy-duty Kubota industrial diesel and low emissions engine
- Standard control module, automatic start of mains failure
- Weather protective and sound attenuated enclosure
- Comprehensive warranty and service
- Outlet - 4 x 15A

TECHNICAL SPECIFICATIONS

Model	PK10S-AU			
Power(ESP)	kVA/kW	11/8.8		
Power(PRP)	kVA/kW	10/8		
Structure Type		RS		
Fuel Consumption	Litre/hour	Fuel consumption100% (of the Prime Power)	3.5 L/h	
		Fuel consumption75% (of the Prime Power)	2.9 L/h	
		Fuel consumption50% (of the Prime Power)	1.8 L/h	
		Fuel consumption25% (of the Prime Power)	N/A	
Fuel Tank Capacity	Litre	100		
Noise Level	dB(A)@7m	64.7		
Dimensions and Weight	Length	Width	Height	Weight
	1932 mm	927 mm	1308 mm	700 kg

ENGINE SPECIFICATIONS

Manufacturer	Kubota
Model	D1105-BG
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	3
Displacement	1123 L
Bore and Stroke	78 mm x 78.4 mm
Compression Ratio	22
Intake Resistance	1.96kPa
Type of Injection	Direct
Total Oil Capacity	5.1 L
Coolant Capacity	6.4 L

PROUDLY 100% AUSTRALIAN OWNED

**MACFARLANE
GENERATORS**
ESTABLISHED 1949

Power Anywhere Anytime | PK10S-AU | 12.2020

MACFARLANEGENERATORS.COM.AU

ALTERNATOR SPECIFICATIONS

Manufacturer	Stamford
Phase	1
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation : Class , temperature rise	H
Degree of protection	IP23
AVR model	
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow	0.11 m ³ /s(50Hz)
-----------------	------------------------------

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

Deep Sea Electronics	DSE4510
----------------------	---------

KEY FEATURES

- Largest back-lit icon display in its class
- Real time clock provides accurate event logging
- Fully configurable via the fascia or PC using USB communication
- Extremely efficient power save mode
- Generator/load power monitoring (kW, kV A, kV Ar, pf)
- Accumulated power monitoring (kW h, kVA h, kVAR h)
- Generator overload protection (kW)
- 4 configurable DC outputs (2 for DSE4510)
- 3 configurable analogue/digital inputs
- 4 configurable digital inputs
- Engine speed protection
- Engine hours counter
- Engine pre-heat
- Engine run-time scheduler
- Battery voltage monitoring
- Start on low battery voltage
- Configurable remote start input
- LCD alarm indication



PROUDLY 100% AUSTRALIAN OWNED

MACFARLANE GENERATORS

ESTABLISHED 1949

POWER ANYWHERE ANYTIME

MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com

SALES | SERVICE | SPARES | HIRE | NEW | USED