PowerLink RK Kubota Series Diesel Generator with Leroy Somer Alternator



Model: PK30S-AU

Frequency: **50Hz**Fuel type: **Diesel**

Powered by: **KUBOTA Engine**

- Powerful heavy-duty Kubota industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service
- Outlet 4 x 15A

TECHNICAL SPECIFICATIONS

Model	PK30S-AU				
Power(ESP)	kVA/kW	33/26.4			
Power(PRP)	kVA/kW	30/24			
Structure Type		R			
Fuel Consumption	Litre/hour	Fuel consumption 10	Fuel consumption 100% (of the Prime Power)		
		Fuel consumption 75	5% (of the Prime Power)	5.9 L/h	
		Fuel consumption 50	0% (of the Prime Power)	4.0 L/h	
		Fuel consumption 25	Fuel consumption 25% (of the Prime Power)		
Fuel Tank Capacity	Litre	180			
Noise Level	dB(A)@7m	65.4	65.4		
Dimensions and Weight	Length	Width	Height	Weight	
	2300 mm	1115 mm	1553 mm	1160 kg	

ENGINE SPECIFICATIONS

Manufacturer	Kubota
Model	V3300-BG
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	3
Displacement	3.318 L
Bore and Stroke	98 mm × 110 mm
Compression Ratio	22.6
Intake Resistance	1.96kPa
Type of Injection	Direct
Total Oil Capacity	13.2L
Coolant Capacity	N/A



ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer
Phase	1
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow	0.11 m ³ /s(50Hz)

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

PowerLink PLC-920

KEY FEATURES

- Key features
- Standard Control Function
- Manual Engine Control Module
- Low Oil Pressure
- High Engine Temperature
- Auxiliary Shutdown
- Over Speed Protection
- Protection Hold-off Timer
- · Charge Failure Warning





MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au I info@macgen.com SALES I SERVICE I SPARES I HIRE I NEW I USED