# POWERLINK EB Baudouin Series Diesel Generator with Leroy Somer Alternator



Model: B375SE3-AU

Frequency: **50Hz**Fuel type: **Diesel** 

Powered by: BAUDOUIN SERIES

415-50Hz-3Phase

- Powerful heavy-duty Baudouin industrial diesel and low emissions engine
- Standard control module, automatic start of mains failure
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service

# **TECHNICAL SPECIFICATIONS**

Model	B375SE3-AU			
Power(ESP)	kVA/kw	400/320		
Power(PRP)	kVA/kw	375/300		
Voltage	V	415		
Fuel Consumption	Litre/hour	Fuel consumption 100% (of the Prime Power)		79.04 L/h
		Fuel consumption	75% (of the Prime Power)	59.57 L/h
		Fuel consumption:	Fuel consumption 50% (of the Prime Power)	
		Fuel consumption:	Fuel consumption 25% (of the Prime Power)	
Fuel Tank Capacity	Litre	1580		
Noise Level	dB(A)@7m	76.8		
Dimensions and Weight	Length	Width	Height	Weight
	4242 mm	1550 mm	2396 mm	4662 kg

# **ENGINE SPECIFICATIONS**

Manufacturer	Baudouin
Model	6M21G2D3/5
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	6
Displacement	12.54 L
Bore and Stroke	127 mm × 165 mm
Compression Ratio	16
Intake Resistance	≦7.0 kPa
Injection Type	High Pressure Common Rail
Total Oil Capacity	30L
Coolant Capacity	16.4 L



# **ALTERNATOR SPECIFICATIONS**

Manufacturer	Leroy Somer LSA47.2S4
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	R250
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



#### **AIR SYSTEM**

Engine Air Flow	1m³/s(50Hz)
-----------------	-------------

Note: All data sheets are for reference only and subject to change without prior notice.

# **CONTROL PANEL**

Powerlink	PLC7420
Powerlink	PLC/420

# **KEY FEATURES**

- Microprocessor control, with high stability and credibility
- Monitoring and measuring operational parameters of the mains supply and genset
- Indicating operation status, fault conditions, all parameters and alarms
- Multiple protections; multiple parameters display, like pressure, temperature, etc...
- Manual, automatic and remote work mode selectable
- Real time clock for time and date display, overall runtime display, 250 log entries
- Overall power output display
- Integral speed/frequency detecting, telling status of start, rated operation, overspeed etc...
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol





# MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED