POWERLINK RK Kubota Series Diesel Generator with Leroy Somer Alternator



Model: GMS18KS-AU

Frequency: **50Hz**Fuel type: **Diesel**

Powered by: **KUBOTA Engine**

415/240V-50Hz-3Phase

- Powerful heavy-duty Kubota industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service
- Outlets 2x 15A, 1x 32A 3PH

TECHNICAL SPECIFICATIONS

Model	GMS18KS-AU			
Power(ESP)	kVA/kW	19.8/15.87		
Power(PRP)	kVA/kW	18/14.4		
Structure Type		RS		
Fuel Consumption	Litre/hour	Fuel consumption1	Fuel consumption 100% (of the Prime Power)	
		Fuel consumption7	'5% (of the Prime Power)	3.0 L/h
		Fuel consumption5	60% (of the Prime Power)	2.0 L/h
		Fuel consumption2	Fuel consumption 25% (of the Prime Power)	
Fuel Tank Capacity	Litre	120		
Noise Level	dB(A)@7m	64.8		
Dimensions and Weight	Length	Width	Height	Weight
	1932 mm	830 mm	1262 mm	736 kg

ENGINE SPECIFICATIONS

Manufacturer	Kubota
Model	D1803-M-DI-BG
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	3
Displacement	1.826 L
Bore and Stroke	87 mm × 102.4 mm
Compression Ratio	23.8
Intake Resistance	1.96kPa
Type of Injection	Direct
Total Oil Capacity	7.6 L
Coolant Capacity	7.1 L



ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer LA40M5
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR	Yes
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow	0.06 m³/s((50Hz)

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

PowerLink PLC-920

KEY FEATURES

- Standard Control Function
- Manual Engine Control Module
- Low Oil Pressure
- High Engine Temperature
- Auxiliary Shutdown
- Over Speed Protection
- Protection Hold-off Timer
- Charge Failure Warning





MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au I info@macgen.com SALES I SERVICE I SPARES I HIRE I NEW I USED