PowerLink RK Kubota Series Diesel Generator with Leroy Somer Alternator



Model: PK45S-AU

Frequency: **50Hz**Fuel type: **Diesel**

Powered by: **KUBOTA Engine**

- Powerful heavy-duty Kubota industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service
- Outlet 4 x 15A

TECHNICAL SPECIFICATIONS

PK45S-AU			
kVA/kW	50/40		
kVA/kW	45/36		
	R		
Litre/hour	Fuel consumption 100% (of the Prime Power)		10.7 L/h
	Fuel consumption 75% (of the Prime Power)		8.2 L/h
	Fuel consumption 50% (of the Prime Power)		5.4 L/h
	Fuel consumption2	Fuel consumption 25% (of the Prime Power)	
Litre	280		
dB(A)@7m	66.0		
Length	Width	Height	Weight
2508 mm	1081 mm	1709 mm	1404 kg
	kVA/kW kVA/kW Litre/hour Litre dB(A)@7m Length	kVA/kW 50/40 kVA/kW 45/36 R Litre/hour Fuel consumption Fuel consumption Fuel consumption Litre 280 dB(A)@7m 66.0 Length Width	kVA/kW 50/40 kVA/kW 45/36 R Litre/hour Fuel consumption100% (of the Prime Power) Fuel consumption5% (of the Prime Power) Fuel consumption50% (of the Prime Power) Fuel consumption25% (of the Prime Power) Litre 280 dB(A)@7m 66.0 Length Width Height

ENGINE SPECIFICATIONS

Manufacturer	Kubota
Model	V3800DI-T-BG
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	4
Displacement	3.769 L
Bore and Stroke	100 mm × 120 mm
Compression Ratio	19.0
Intake Resistance	1.96kPa
Type of Injection	Direct
Total Oil Capacity	13.2 L
Coolant Capacity	8.2 L



ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer
Phase	1
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR model	
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

For all and All Floor	044 2 /- /501 >
Engine Air Flow	0.11 m ³ /s(50Hz)

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

PowerLink PLC-920

KEY FEATURES

- Standard Control Function
- Manual Engine Control Module
- Low Oil Pressure
- High Engine Temperature
- Auxiliary Shutdown
- Over Speed Protection
- Protection Hold-off Timer
- Charge Failure Warning





MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au I info@macgen.com SALES I SERVICE I SPARES I HIRE I NEW I USED